

Tire Size	Ply Rating	Load Range	Load Index	SR	Meas. Rim	S.W.	
						in	mm
ST175/80R13 6PR	6	C	91	Q	5.00B	7.0	177
ST205/75R14 6PR	6	C	100	Q	5.5J	8.0	203
ST215/75R14 6PR	6	C	102	Q	6J	8.5	216
ST205/75R15 6PR	6	C	101	Q	5.5J	8.0	203
ST205/75R15 8PR	8	D	107	Q	5.5J	8.0	203
ST225/75R15 8PR	8	D	113	Q	6J	8.8	223
ST225/75R15 10PR	10	E	117	Q	6J	8.8	223
ST235/80R16 10PR	10	E	123	Q	6.5J	9.3	235

O.D.		Max. Load		Maximum Pressure		Tread Depth		RPM
		Single						
in	mm	lbs	kg	psi	kpa	32nd	mm	
24.0	610	2989	1356	50	350	10	8	160
27.1	689	3889	1764	50	350	10	8	160
26.7	678	1870	850	50	350	10	8	160
27.1	689	4010	1819	50	350	10	8	160
27.1	689	4740	2150	65	450	10	8	160
28.3	719	5589	2535	65	450	10	8	160
28.3	719	6221	2822	80	550	10	8	160
30.8	782	7533	3417	80	550	10	8	160

Weight		40' HC qty
lbs	kg	
17.6	8	1600
21.61	9.80	1300
22.05	10.00	1150
24.91	11.30	1150
24.91	11.30	1150
28.15	12.77	970
28.66	13.00	970
35.71	16.20	760